



Clack WS1.50CI 1 1/2"
Steuerventil

Mengen- und zeitgesteuert
mit elektronischem Timer

Ausführliche Historiefunktion

Gesamtkapazität- sowie
Reservekapazitätsberechnung

Enthärter oder Filterventil
empfohlen für Drucktanks 10" - 30"
Arbeitsdruck von 1,4 bis 8,6 bar
Arbeitstemperatur von 4 bis 43°C

Water Specialist 1 .5" CI Control Specifications

Inlet/Outlet (1)	1.5" FPT
Cycles	up to 9
Valve Material	Lead free brass
Regeneration	Downflow
FLOW RATES	
Service @15 psi/1 bar drop (includes meter)	60 gpm (227 lpm)
Backwash @ 25 psi/1.7 bar drop	50 gpm (189 lpm)
OPERATING PRESSURES	
Minimum/Maximum	20 - 125 psi (1.4 - 8.6 bar)
OPERATING TEMPERATURES	
Minimum/Maximum	40° - 110° F (4° - 43° C)
METER	
Accuracy	± 5%
Flow Rate Range	0.5 - 60 gpm (2 - 227 lpm)
Volume Range	0.02 to 2000.0 m ³
Totalizer	1 - 99,999 m ³
DIMENSIONS & WEIGHT	
Distributor Pilot	
Valve bodies with female 1.5" NPT Inlet & Outlet	1.90" OD (1.5" NPS)
Valve bodies with female 1.5" BSPT Inlet & Outlet	50 mm OD
Drain Line (2)	1.25" FPT
Brine Line	¾" FPT
Adapters Available	½" OD Poly Tube
Mounting Base	4" - 8 UN
Height From Top Of Tank	7.5" (191 mm)
Shipping Weight With Meter	21 lbs. (9.5 kg)
ELECTRICAL SPECIFICATIONS	
	AC Adapter
	<u>U.S.</u> <u>International</u>
Supply Voltage	120V AC 230V AC
Supply Frequency	60 Hz 50 Hz
Output Voltage	12V AC 12V AC
Output Current	500 mA 500 mA
TANK APPLICATIONS	
Water Softener	10" - 30" Diameter
Water Filter (3)	10" - 30" Diameter
CYCLE S OF OPERATION	
Choose up to nine regeneration cycles, in any order, with a wide range of available values:	
Cycle	Range of values
Backwash	1 - 120 minutes
Rinse	1 - 120 minutes
Pause (service)	1 - 480 minutes
Brine (co-current)	1 - 180 minutes
Refill (softener)	0.05 - 95.00 Kg
Refill (filter)	0.05 - 95.00 Liters

Options: Backwash Filter, Weather Cover

Compatible with the following typical concentrations of regenerants or chemicals: Sodium chloride, potassium chloride, potassium permanganate, sodium bisulfite, chlorine and chloramines

1. See Distributor Pilot.

2. Casting comes with a 1.25" FPT drain connection. An adapter is provided to accept existing WS1 drain line flow controls up to 25 gpm.

3. Filter tank size calculated @ 10 gpm of backwash per square foot of bed area/407 lpm per m² of bed area